



Triax UK Limited,
Abergorki Ind. Est,
RCT, South Wales,
CF42 6DL

Tel: 0845 601 0578

Email: sales@triax.co.uk

www.triax.co.uk



HDMI CABLE

- Professional grade HDMI cable for a perfect high definition connection.
- Sealed moulded diecast connectors.
- Gold plated contacts for quality transmission and tarnish resistance.
- EMI interference suppressed.
- Compatible with all HD resolutions including 720p, 1080i and 1080p video formats.
- Ideal for connecting SkyHD boxes, DVD players and all other HDMI equipped AV equipment.

Simply **more**
- more simply

Part No			370710	370711	370712	370713	370714
CABLE							
Length		m	3	5	10	15	20
Ferrite			2	2	2	2	2
Signal Pairs	Conductor		Tinned Copper	Tinned Copper	Tinned Copper	Tinned Copper	Tinned Copper
	Conductor Size	AWG	28	28	28	28	26
	Insulation Material		Foamed PE	Foamed PE	Foamed PE	Foamed PE	Foamed PE
	Insulation Core Colours		White/Green	White/Green	White/Green	White/Green	White/Green
			White/Brown	White/Brown	White/Brown	White/Brown	White/Brown
			White/Blue	White/Blue	White/Blue	White/Blue	White/Blue
			White/Red	White/Red	White/Red	White/Red	White/Red
	Drain Wire		Tinned Copper	Tinned Copper	Tinned Copper	Tinned Copper	Tinned Copper
	Drain Wire Size	AWG	28	28	28	28	26
	Shield		AL/Mylar/Mylar	AL/Mylar/Mylar	AL/Mylar/Mylar	AL/Mylar/Mylar	AL/Mylar/Mylar
Signal Wire	Conductor		Tinned Copper	Tinned Copper	Tinned Copper	Tinned Copper	Tinned Copper
	Conductor Size	AWG	28	28	28	28	26
	Insulation Material		HDPE	HDPE	HDPE	HDPE	HDPE
	Insulation Core Colours		White	White	White	White	White
			Green	Green	Green	Green	Green
			Orange	Orange	Orange	Orange	Orange
			Yellow	Yellow	Yellow	Yellow	Yellow
			Red	Red	Red	Red	Red
			Purple	Purple	Purple	Purple	Purple
Outer Shield	Shield 1		Aluminium Mylar	Aluminium Mylar	Aluminium Mylar	Aluminium Mylar	Aluminium Mylar
	Shield 2		Tinned Copper (braiding)	Tinned Copper (braiding)	Tinned Copper (braiding)	Tinned Copper (braiding)	Tinned Copper (braiding)
Outer Jacket	Overall Diameter	mm	Ø 7.3	Ø 7.3	Ø 7.3	Ø 7.3	Ø 8
	Material		PVC	PVC	PVC	PVC	PVC
ELECTRICAL							
Differential Impedance		Ohms	100 +/- 10%	100 +/- 10%	100 +/- 10%	100 +/- 10%	100 +/- 10%
Max Differential Delay		ns/m	5.05	5.05	5.05	5.05	5.05
Max Intra - Pair Skew		ps	151	151	151	151	151
Far-end Crosstalk (@ 1-5000 MHz)		dB	-26	-26	-26	-26	-26
CONNECTOR							
Pin			19	19	19	19	19
			Gold Plated	Gold Plated	Gold Plated	Gold Plated	Gold Plated
Metal Shell			Pearl Chrome Plated	Pearl Chrome Plated	Pearl Chrome Plated	Pearl Chrome Plated	Pearl Chrome Plated
Connector Impedance		Ohms	100 +/- 15%	100 +/- 15%	100 +/- 15%	100 +/- 15%	100 +/- 15%

*Triax reserves the right to change the specifications without prior notification